

10/777140

Hit List

First Hit Your wildcard search against 10000 terms has yielded the results below.

Your result set for the last L# is incomplete.

The probable cause is use of unlimited truncation. Revise your search strategy to use limited truncation.

[Clear](#)[Generate Collection](#)[Print](#)[Fwd Refs](#)[Bkwd Refs](#)[Generate OACS](#)

Search Results - Record(s) 1 through 6 of 6 returned.

☐ 1. Document ID: US 4694808 A

L5: Entry 1 of 6

File: USPT

Sep 22, 1987

US-PAT-NO: 4694808

DOCUMENT-IDENTIFIER: US 4694808 A

TITLE: Method and fuel injection system for fuel supply to a mixture-compressing internal combustion engine having externally supplied ignition

Full	Title	Citation	Front	Review	Classification	Date	Reference	Sequence	Abstract	Claims	KMC	Draw D
------	-------	----------	-------	--------	----------------	------	-----------	----------	----------	--------	-----	--------

☐ 2. Document ID: US 4168685 A

L5: Entry 2 of 6

File: USPT

Sep 25, 1979

US-PAT-NO: 4168685

DOCUMENT-IDENTIFIER: US 4168685 A

TITLE: Fuel metering device for internal combustion engines and fuel systems incorporating such device

Full	Title	Citation	Front	Review	Classification	Date	Reference	Sequence	Abstract	Claims	KMC	Draw D
------	-------	----------	-------	--------	----------------	------	-----------	----------	----------	--------	-----	--------

☐ 3. Document ID: US 3866583 A

L5: Entry 3 of 6

File: USPT

Feb 18, 1975

US-PAT-NO: 3866583

DOCUMENT-IDENTIFIER: US 3866583 A

TITLE: MIXTURE CONTROL SYSTEM FOR AN INTERNAL COMBUSTION ENGINE WITH CONTROLLED INJECTION FUEL

Full	Title	Citation	Front	Review	Classification	Date	Reference	Sequence	Abstract	Claims	KMC	Draw D
------	-------	----------	-------	--------	----------------	------	-----------	----------	----------	--------	-----	--------

☐ 4. Document ID: US 2608054 A

L5: Entry 4 of 6

File: USOC

Aug 26, 1952

US-PAT-NO: 2608054

DOCUMENT-IDENTIFIER: US 2608054 A

TITLE: Air turbine starting means for gas turbine power plants

DATE-ISSUED: August 26, 1952

INVENTOR-NAME: PRICE NATHAN C

US-CL-CURRENT: 60/787; 290/4C, 417/408

Full	Title	Citation	Front	Review	Classification	Date	Reference	Sequences	Attachments	Claims	KWIC	Draw. De
------	-------	----------	-------	--------	----------------	------	-----------	-----------	-------------	--------	------	----------

☐ 5. Document ID: US 2540991 A

L5: Entry 5 of 6

File: USOC

Feb 6, 1951

US-PAT-NO: 2540991

DOCUMENT-IDENTIFIER: US 2540991 A

TITLE: Gas reaction aircraft power plant

DATE-ISSUED: February 6, 1951

INVENTOR-NAME: PRICE NATHAN C

US-CL-CURRENT: 244/209; 123/41.7, 244/103S, 244/15, 244/202, 244/50, 244/53R,
244/60, 244/74, 415/179, 415/199.4, 415/914, 417/338, 417/390, 417/408, 475/50,
60/243, 60/244, 60/263, 60/264, 60/266, 60/39.281, 60/39.37, 60/793, 62/241

Full	Title	Citation	Front	Review	Classification	Date	Reference	Sequences	Attachments	Claims	KWIC	Draw. De
------	-------	----------	-------	--------	----------------	------	-----------	-----------	-------------	--------	------	----------

☐ 6. Document ID: US 2514513 A

L5: Entry 6 of 6

File: USOC

Jul 11, 1950

US-PAT-NO: 2514513

DOCUMENT-IDENTIFIER: US 2514513 A

TITLE: Jet power plant with boundary layer control for aircraft

DATE-ISSUED: July 11, 1950

INVENTOR-NAME: PRICE NATHAN C

US-CL-CURRENT: 244/15; 244/103R, 244/208, 244/209, 244/62, 244/74, 416/171, 60/243,
60/264, 60/267, 60/786

Full	Title	Citation	Front	Review	Classification	Date	Reference			Claims	KWIC	Drawn De
------	-------	----------	-------	--------	----------------	------	-----------	--	--	--------	------	----------

Clear	Generate Collection	Print	Fwd Refs	Bkwd Refs	Generate OACS
-------	---------------------	-------	----------	-----------	---------------

Terms	Documents
L4 and (reduc\$ with fuel\$ with suppl\$ with fuel\$ with (pass\$ or exceed\$ or over\$))	6

Display Format:

[Previous Page](#) [Next Page](#) [Go to Doc#](#)

[First Hit](#) [Fwd Refs](#)[Previous Doc](#)[Next Doc](#)[Go to Doc#](#)

Generate Collection

Print

L5: Entry 1 of 6

File: USPT

Sep 22, 1987

US-PAT-NO: 4694808

DOCUMENT-IDENTIFIER: US 4694808 A

TITLE: Method and fuel injection system for fuel supply to a mixture-compressing internal combustion engine having externally supplied ignition

DATE-ISSUED: September 22, 1987

INVENTOR-INFORMATION:

NAME	CITY	STATE	ZIP CODE	COUNTRY
Peters; Klaus-Jurgen	Affalterbach			DE

ASSIGNEE-INFORMATION:

NAME	CITY	STATE	ZIP CODE	COUNTRY	TYPE CODE
Robert Bosch GmbH	Stuttgart			DE	03

APPL-NO: 06/410099 [PALM]

DATE FILED: August 20, 1982

FOREIGN-APPL-PRIORITY-DATA:

COUNTRY	APPL-NO	APPL-DATE
DE	3140948	October 15, 1981

INT-CL-ISSUED: [04] F02M 39/00

US-CL-ISSUED: 123/453; 123/454

US-CL-CURRENT: 123/453; 123/454

FIELD-OF-CLASSIFICATION-SEARCH: 123/453, 123/454, 123/452, 123/299, 123/447
See application file for complete search history.

PRIOR-ART-DISCLOSED:

U.S. PATENT DOCUMENTS

Search Selected

Search ALL

Clear

	PAT-NO	ISSUE-DATE	PATENTEE-NAME	US-CL
<input type="checkbox"/>	<u>3994273</u>	November 1976	Stumpp	123/454
<input type="checkbox"/>	<u>4161964</u>	July 1979	Greiner et al.	123/447
<input type="checkbox"/>	<u>4214565</u>	July 1980	Knapp et al.	123/454
<input type="checkbox"/>	<u>4257375</u>	March 1981	Ulrich	123/453

<input type="checkbox"/>	<u>4326487</u>	April 1982	Maisch et al.	123/453
<input type="checkbox"/>	<u>4354472</u>	October 1982	Knapp et al.	123/454
<input type="checkbox"/>	<u>4381751</u>	May 1983	Maisch et al.	123/454

FOREIGN PATENT DOCUMENTS

FOREIGN-PAT-NO	PUBN-DATE	COUNTRY	CLASS
2754373	June 1979	DE	123/453

ART-UNIT: 342

PRIMARY-EXAMINER: Feinberg; Craig R.

ATTY-AGENT-FIRM: Greigg; Edwin E.

ABSTRACT:

A method and a fuel injection system for supplying fuel to a mixture-compressing internal combustion engine having externally supplied ignition is proposed. The fuel injection system includes metering valves, downstream of which regulating valves are disposed and at one side of which the fuel pressure downstream of the metering valves prevails and on the other side of which the fuel pressure in a control pressure line prevails. The control pressure line communicates with the fuel supply line and is limited by a control throttle and a return-flow throttle; from it, a branch line leads to an electromagnetic supplementary injection valve, by way of which further fuel, in addition to the fuel injected via injection valves, can be injected. The triggering of the supplementary injection valve can be effected by an electronic control unit for injecting fuel during cold starting of the engine or in the presence of a measurement signal characterizing an acceleration of the engine. By means of the triggering of the supplementary injection valve, the pressure in the control pressure line is reduced, as a result of which--because of an increase in the pressure difference at the metering valves--a greater fuel quantity is metered.

9 Claims, 1 Drawing figures

[Previous Doc](#) [Next Doc](#) [Go to Doc#](#)

[First Hit](#) [Fwd Refs](#)[Previous Doc](#)[Next Doc](#)[Go to Doc#](#)

Generate Collection

Print

L5: Entry 1 of 6

File: USPT

Sep 22, 1987

DOCUMENT-IDENTIFIER: US 4694808 A

TITLE: Method and fuel injection system for fuel supply to a mixture-compressing internal combustion engine having externally supplied ignition

Abstract Text (1):

A method and a fuel injection system for supplying fuel to a mixture-compressing internal combustion engine having externally supplied ignition is proposed. The fuel injection system includes metering valves, downstream of which regulating valves are disposed and at one side of which the fuel pressure downstream of the metering valves prevails and on the other side of which the fuel pressure in a control pressure line prevails. The control pressure line communicates with the fuel supply line and is limited by a control throttle and a return-flow throttle; from it, a branch line leads to an electromagnetic supplementary injection valve, by way of which further fuel, in addition to the fuel injected via injection valves, can be injected. The triggering of the supplementary injection valve can be effected by an electronic control unit for injecting fuel during cold starting of the engine or in the presence of a measurement signal characterizing an acceleration of the engine. By means of the triggering of the supplementary injection valve, the pressure in the control pressure line is reduced, as a result of which--because of an increase in the pressure difference at the metering valves--a greater fuel quantity is metered.

Application Filing Date (1):

19820820

DATE ISSUED (1):

19870922

Brief Summary Text (2):

The invention relates to a method as generally defined hereinafter and also to a fuel injection system. A method and a fuel injection apparatus are already known in which when the engine is started, fuel is injected into the air intake tube of the engine via a supplementary, electromagnetically actuated injection valve. In order to enrich the fuel-air mixture at predetermined operating conditions of the engine, it is known to increase the pressure drop at the metering valves by reducing a control pressure by means of an electromagnetically actuatable control pressure valve.

Brief Summary Text (4):

The method according to the present invention in which a fuel injection system for supplying fuel to a mixture-compressing internal combustion engine having externally supplied ignition has the advantage over the prior art in that a high enrichment factor for the fuel-air mixture can be attained at reduced expense by using only a single supplementary, electromagnetically actuatable injection valve.

Brief Summary Text (5):

Advantageous further embodiments of and improvements to the fuel injection system disclosed hereinafter can be attained by means of supplementary sensing and control operations.

Detailed Description Text (4):

A line 19 branches off from the fuel supply line 3 and discharges via a control throttle 20 into a control pressure line 21. Downstream of the control throttle 20 in the control pressure line 21 are the control chambers 15 of the regulating valves 13, and downstream of the control chambers 15 there is a return-flow throttle 24. Also branching off from the fuel supply line 3 is a line 25 in which a pressure regulating valve 26 is disposed for maintaining a constant fuel pressure upstream of the fuel metering valves 1. The pressure regulating valve 26 shown by way of example in the drawing has a regulating piston 27 which can be displaced counter to the force of a regulating spring 28 by the pressure of the fuel in the line 25 so that fuel can flow over a regulating edge 29 out of the line 25 into a return-flow line 30 and back to the fuel container 6. A blocking valve 31 can simultaneously be opened by the regulating piston 27 as it effects an opening operation. To this end, the regulating piston 27, as it effects an opening operation and while the fuel pump 5 is pumping, engages an actuation pin 32, which displaces the movable valve element 33 of the blocking valve 31 in the opening direction, counter to the force of a blocking spring 34. If the engine is shut off, then no further fuel supply is effected via the electric fuel pump 4, 5, and the pressure regulating valve 26 closes. At the same time, the blocking spring 34 engaging the actuation pin 32 displaces the movable valve element 33 of the blocking valve 31 into the closing position.

Detailed Description Text (5):

Downstream of the return-flow throttle 24 the fuel reaches the return-flow line 30 in which the blocking valve 31 is also disposed. When the fuel pump is not pumping, the closed blocking valve 31 prevents fuel from leaking out of the control pressure line 31, and thus allows the fuel injection system to remain filled with fuel for the next time the engine is started.

Detailed Description Text (6):

From the control pressure line 21 downstream of the control throttle 20, a branch line 36 leads via a limitation throttle 37 to an electromagnetically actuatable supplementary injection valve 38, by way of which fuel can be injected into the air intake tube 47 or into the intake manifold 39 upstream of the individual intake tubes 22. The supplementary injection valve 38 is triggerable by means of an electronic control unit 41 which is supplied by the vehicle battery 43 via an ignition switch 42. In addition to the engine temperature being ascertained by means of a temperature sensor 44, a measurement signal 45 characterizing an acceleration of the engine can be fed to the electronic control unit 41. The measurement signal 45 is ascertained in a known manner, for instance by means of a differentiating pressure switch (not shown), which responds to a variation in the pressure drop at the throttle valve 46 in the air intake tube 47.

Detailed Description Text (7):

By means of the supplementary injection valve 38, a supplementary quantity of fuel can be injected into the air intake tube 47 or the intake manifold 39 in a known manner, in accordance with engine temperature for a limited time period during a cold start of the engine, which effects an enrichment of the fuel-air mixture, and makes for reliable starting of the engine. The supplementary injection valve 38 can be furthermore triggered by the electronic control device in such a manner that it opens whenever a measurement signal 45 characterizing engine acceleration is present at the electronic control unit 41. The opening of the supplementary injection valve 38 effects not only an enrichment of the fuel-air mixture because of the injection of fuel by way of the supplementary injection valve 38, but it also simultaneously effects a reduction of pressure in the control pressure line 21; this unique operation results in an identical reduction of pressure in the regulating chambers 12 of the regulating valves 13, thus increasing the pressure difference at the metering valves 1 and causing the metering of a greater quantity of fuel. The enrichment of the fuel-air mixture is thus effected simultaneously via an increased quantity of fuel injected via the injection valves 18 and a

supplementary fuel quantity injected via the supplementary injection valve 38. As a result, a very high enrichment rate can be attained.

CLAIMS:

1. A method for supplying fuel to a mixture-compressing internal combustion engine having an air intake tube and externally supplied ignition by means of a fuel injection system having metering valve means disposed in a fuel supply line for metering a quantity of fuel at a specific proportion to the quantity of air aspirated by said engine, a control pressure line communicating with said fuel supply line, and having individual injection valve means, comprising the steps of:

injecting the metered fuel ahead of each cylinder of said engine; and

further injecting fuel into the air-intake tube of said engine by means of a supplementary injection valve means in accordance with engine operating characteristics, whereby the pressure in said control pressure line is reduced by means of said supplementary injection valve means, and the pressure difference at said metering valve means is increased to thereby increase the metered fuel quantity transmitted by means of said individual injection valve means.

2. A method for supplying fuel to a mixture-compressing internal combustion engine having an air intake tube and externally supplied ignition by means of a fuel injection system having metering valve means disposed in a fuel supply line for metering a quantity of fuel at a specific proportion to the quantity of air aspirated by said engine, the metering being effected at a pressure difference which is constant yet can be varied in accordance with operating characteristics of the engine, a movable valve element of a regulating valve disposed downstream of each of said metering valve means for regulating the pressure difference at each of said metering valve means, a control pressure line which communicates with said fuel supply line and is limited at one end by a control throttle means and at the other end by a return-flow throttle means and leads to a return-flow line, and having individual injection-valve means, comprising the steps of:

injecting the metered fuel ahead of each cylinder of said engine; and

further injecting fuel into the air-intake tube of said engine by means of a supplementary injection valve means in accordance with engine operating characteristics, whereby the pressure in said control pressure line is reduced by means of the supplementary injection valve means, and the pressure difference at said metering valve means is increased to thereby increase the metered fuel quantity transmitted by means of said individual injection valve means.

3. A method as defined by claim 2, wherein said supplementary injection valve, for enrichment of the fuel-air mixture, is electromagnetically actuatable and triggerable in accordance with control signals characterizing an acceleration of said engine.

4. A method as defined by claim 2, wherein said supplementary injection valve, for enrichment of the fuel-air mixture, is electromagnetically actuatable and triggerable upon the starting of said engine.

5. A fuel injection system for supplying fuel to a mixture-compressing internal combustion engine having an air intake tube and externally supplied ignition comprising:

metering valve means disposed in a fuel supply line for metering a quantity of fuel at a specific proportion to the quantity of air aspirated by said engine,

a movable valve element of a regulating valve means disposed downstream of each of

said metering valves for regulating the pressure difference at each of said metering valve means,

a control pressure line communicating with said fuel supply line,

a control throttle means at one end of said control pressure line,

a return-flow throttle means at the other end of said control pressure line,

individual injection valve means positioned ahead of each cylinder of said engine and connected to said fuel supply line by means of said regulating valve means, and

a supplementary injection valve means connected to said control pressure line, whereby fuel can be additionally injected into the air-intake tube of said engine in accordance with engine operating characteristics.

7. A system as defined by claim 5, wherein said supplementary injection valve means for the injection of fuel is triggerable by means of control signals responsive to an acceleration of said engine.

8. A system as defined by claim 5, wherein said supplementary injection valve means for the injection of fuel is triggerable by means of control signals responsive to the starting of said engine.

[Previous Doc](#)

[Next Doc](#)

[Go to Doc#](#)

[First Hit](#) [Fwd Refs](#)[Previous Doc](#)[Next Doc](#)[Go to Doc#](#)

Generate Collection

Print

L5: Entry 2 of 6

File: USPT

Sep 25, 1979

US-PAT-NO: 4168685

DOCUMENT-IDENTIFIER: US 4168685 A

TITLE: Fuel metering device for internal combustion engines and fuel systems
incorporating such device

DATE-ISSUED: September 25, 1979

INVENTOR-INFORMATION:

NAME	CITY	STATE	ZIP CODE	COUNTRY
Little, deceased; Allan V.	LATE OF Cheltenham			AU
Little, administratrix; by Anna	Cheltenham, Victoria			AU
Wilkinson; Ronald A.	Beaumaris, Victoria	3193		AU

APPL-NO: 05/666448 [PALM]

DATE FILED: March 12, 1976

FOREIGN-APPL-PRIORITY-DATA:

COUNTRY	APPL-NO	APPL-DATE
AU	PC0905	March 14, 1975

INT-CL-ISSUED: [02] F02M 31/00, F02M 17/18

US-CL-ISSUED: 123/133; 261/44C, 261/16

US-CL-CURRENT: 123/575; 123/525, 123/527, 123/557, 261/16, 261/44.4FIELD-OF-CLASSIFICATION-SEARCH: 123/133, 123/127, 123/120, 123/121, 261/44R,
261/16, 261/145, 261/144, 261/5A, 261/44C, 48/18C
See application file for complete search history.

PRIOR-ART-DISCLOSED:

U.S. PATENT DOCUMENTS

Search Selected

Search ALL

Clear

	PAT-NO	ISSUE-DATE	PATENTEE-NAME	US-CL
<input type="checkbox"/>	<u>1147608</u>	July 1915	Clark	123/133
<input type="checkbox"/>	<u>1688947</u>	October 1928	Thomas	261/16
<input type="checkbox"/>	<u>2152501</u>	March 1939	Robinson	123/121
<input type="checkbox"/>	<u>2645906</u>	July 1953	Ryan	123/121
<input type="checkbox"/>	<u>2882882</u>	April 1959	Pantano	123/122F

<input type="checkbox"/> <u>3602202</u>	August 1971	Kobayashi	261/16
<input type="checkbox"/> <u>3738334</u>	June 1973	Farr	123/122E
<input type="checkbox"/> <u>3753555</u>	August 1973	Lawrence	261/44C
<input type="checkbox"/> <u>3832985</u>	September 1974	Edde	123/122A
<input type="checkbox"/> <u>3930476</u>	January 1976	Koch	123/122A

FOREIGN PATENT DOCUMENTS

FOREIGN-PAT-NO	PUBN-DATE	COUNTRY	CLASS
785902	August 1935	FR	123/133
937272	April 1948	FR	165/52
945760	May 1949	FR	261/16

ART-UNIT: 342

PRIMARY-EXAMINER: Lazarus; Ronald H.

ATTY-AGENT-FIRM: Shlesinger, Arkwright, Garvey & Dinsmore

ABSTRACT:

A fuel metering device for an internal combustion engine, and in which a metering needle, common to a liquid and gaseous fuel chambers having respective inlets for communication with a respective source of liquid and gaseous fuel for the engine, extends between the outlet of the liquid fuel chamber and one of the inlet and the outlet of the gaseous fuel chamber and has thereat a respective valving member adapted for controlling the volume of fuel metered to the engine induction system; and an engine having such device incorporated in the fuel induction system thereof.

30 Claims, 5 Drawing figures

[Previous Doc](#) [Next Doc](#) [Go to Doc#](#)